

Code	Description	Size	Colour
37013	Gorilla Solvent Cleaner	1Lt	N/A
20125	Gorilla Solvent Cleaner	4Lt	N/A
20126	Gorilla Solvent Cleaner	20Lt	N/A

1. Description

Gorilla Solvent Cleaner is used for removing greasy marks. Gorilla Solvent Cleaner is unlikely to affect any powder coated surfaces however preliminary tests are recommended.

2. Characteristics

- Extra quick evaporation
- Excellent clean up
- Removes grease marks

3. Technical Data

Base:	Solvent
Colour:	Clear
Consistency:	Liquid

4. Applications

- Cleaning & Degreasing of Non-Porous Surfaces
- Removing oily/greasy residues

5. Packaging

Plastic containers of 1Lt, 4Lt 20 Lt

6. Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

7. Application Instructions

Method: Wipe on, wipe off and surface will be clean.

Application Limitations

- KEEP AWAY FROM RUBBER SURFACES AND GASKETS AS GORILLA SOLVENT CLEANER MAY ATTACK.
- Always test on powder-coat in a small unobtrusive area to ensure that you are pleased with the result, before continuing
- Test is always best as although initial tests have been completed and show no effect, we cannot guarantee this for all surfaces.

Due to the range of substrates on the market recommend preliminary compatibility tests prior to commencement of application.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene
- Gorilla Solvent Cleaner is flammable (flash point 36°C), can form explosive mixtures with air and is immiscible (WILL NOT MIX WITH WATER) with water. It should be kept away from sources of heat, naked flames and sparks. Electrostatic charge may be generated during handling eg. pumping. Earth container and pipes containing solvent to stop charge. In case of fire, use foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth should be used for small fires only.
- We highly recommend a preliminary compatibility test.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email sales@soudal.co.nz.***

Last Updated: 25 October 2019

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	Fax: (07) 847 0324
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz