



PACK SIZES

Underfloor Insulation Sections

Mammoth underfloor insulation are self-supporting medium density pads that squeeze into place between joists without staples or other fixings.

Cut to a variety of widths, Mammoth® polyester underfloor insulation sections are moisture resistant, high performance options that are safer to install than stapled solutions.

PRODUCT RANGE

			TACK SIZES					
	Concentration of the second se	BRANZ Appraised Appraised No. 802	Density (kg/m3)	R-Value	Nominal thickness (mm)	Dimensions	Pieces per pack	Area per pack (m2)
Underfloor Sections	\checkmark	\checkmark	16.67	R 1.9	90	370mm x 1140mm	16	6.75
	\checkmark	\checkmark	16.67	R 1.9	90	425mm x 1140mm	16	7.75
	\checkmark	\checkmark	16.67	R 1.9	90	475mm x 1140mm	14	7.58
	\checkmark	\checkmark	16.67	R 1.9	90	580mm x 1140mm	12	7.93
		\checkmark	15	R 2.8	140	370mm x 1140mm	10	4.21
		\checkmark	15	R 2.8	140	425mm x 1140mm	10	4.84
		\checkmark	15	R 2.8	140	475mm x 1140mm	10	5.41
		\checkmark	15	R 2.8	140	580mm x 1140mm	8	5.28
Double Layer - R 1.9 x 2	\checkmark		16.67	R 3.8	180	370mm x 1140mm	16	6.75*
	\checkmark		16.67	R 3.8	180	425mm x 1140mm	16	7.75*
	\checkmark		16.67	R 3.8	180	475mm x 1140mm	14	7.58*
	\checkmark		16.67	R 3.8	180	580mm x 1140mm	12	7.93*

* Double Layering - Double the quantity of product is required. For instance, a 100m2 area requires 200m2 of product to achieve a double layer.

KEY FEATURES

- High performance, semi-rigid Airlay polyester sections.
- Long-lasting underfloor insulation.
- Sections can easily be cut using wide blade craft knives or specialised insulation saws.
- Easy and safer to install simply squeezes between joists and is self-supporting.
- Non-corrosive will not affect electrical wiring underfloor.
- Moisture resistant underfloor.
- Heat bonded will not sag or shrink over time.
- Red List Free no glues, resins, formaldehyde or pesticides added.
- Non-irritant and non-toxic so no precautions are required for handling the product.
- Mammoth Underfloor Sections are BRANZ appraised.
- Performance warranted for 50 years (T&Cs apply).
- Made in New Zealand by a carboNZero certified organisation.

TECHNICAL DETAILS

Technical Attributes	Standard	Test Result		
New Zealand Building Code				
✓ Durability	Clause B2.3.1 a) 15 years Clause B2.3.1 b) 50 years	Ref: BRANZ Appraisal No 802 ¹		
 Internal Moisture 	Clause E3.3.1	Ref: BRANZ Appraisal No 802 ¹		
 Hazardous Building Materials 	Clause F2.3.1	Ref: BRANZ Appraisal No 802 ¹		
 Energy Efficiency 	Clause H1.3.1(a) Clause H1.3.2 E	Ref: BRANZ Appraisal No 802 ¹		
Product Safety				
 Non Toxic 	OSH Health and Safety Guidelines ²	Polyester products are 'non-toxic'		
 Non Irritant 	OSH Health and Safety Guidelines ²	Polyester products are 'non-irritant'		
 Respiratory Safe 	n/a	Polyester fibres are non-respirable		
✓ Fire Test	ISO9705	Group1S		
✓ VOC Emission Safe ³	Total VOC \leq 0.5mg/m ³	< 0.005 mg/m ³ - level below detection ⁴		
	Formaldehyde ≤ 0.06 mg/m ³	< 0.009mg/m ³ - level below detection		
✓ Glue Free		Free from all glues		
✓ OTHER				
✓ Non Corrosive	AS/NZS4859.1	Materials composed entirely of polyester are regarded as non-corrosive and are exempt from testing. Alkalinity of pH 7.8.		
 Vermin Resistant 		Not a food source for vermin (and not treated)		

1 Meet or contribute to these provisions when designed, used, installed and maintained in accordance with BRANZ Appraisal 802.

2 Occupational Safety and Health Service. Health and Safety Guidelines for the Selection and Safe Handling of Synthetic Mineral Fibres. Dept, of Labour, 1994, p18. 3 Mammoth has been tested under ASTM D5116. Based on test results for a product with similar nominal weight.

4 All individual VOCs were less than their threshold limit values. Carcinogens and reproductive toxins were not identified as part of the VOCs.

INSTALLATION & WARRANTY

Installation

Mammoth Underfloor Insulation Sections must be installed according to the manufacturer's guidelines and in accordance with NZS 4246 (Energy Efficiency - Installing Insulation in Residential Buildings). Installation Instructions for Mammoth Underfloor Insulation Sections can be found at www.mammoth.co.nz/downloads Contact us on 0800 MAMMOTH for more details.

50 Year Warranty

Mammoth Insulation has a 50 year warranty. Our product warranty covers that - so long as the insulation is installed correctly and remains adequately protected - Mammoth insulation will perform for 50 years. The warranty applies only to 100% polyester insulation products manufactured by InZone Industries Ltd and not to other composite products manufactured by InZone Industries Ltd. Read the full warranty at <u>www.mammoth.co.nz/downloads</u> for terms and conditions.

BRANZ Appraised

Mammoth Underfloor Insulation Sections have been tested by, and is covered by BRANZ Appraisal 802.



Correct as at 06 June 2022



0800 MAMMOTH

www.mammoth.co.nz

Manufactured in New Zealand's North Island and South Island PO Box 204 289, Highbrook, Auckland 2161 Ph: 0800 626 668 | E: info@mammoth.co.nz *Registered trade mark of InZone Industries Ltd