



Thermal Pads

GreenStuf® THERMAL PADS are 100% polyester semi-rigid thermal insulation segments pre-cut to fit common timber framed walls, ceilings and mid-floor joist spacings.

Applications

GreenStuf® THERMAL PADS are designed for the thermal insulation of timber framed buildings in accordance with NZBC H1 Energy Efficiency requirements. GreenStuf® THERMAL PADS can be used in ceilings, internal and external walls and mid-floor cavities. To ensure Building Code compliance Autex Insulation recommends that Architects and building designers consult the relevant NZ Standards before specifying thermal insulation products:

- NZBC H1/AS1 Energy Efficiency, 2.0 Building Thermal Envelope
- NZBC G6/VM1 Airborne and Impact Sound
- NZS 4218: Thermal Insulation - Housing and Small Buildings
- NZS 4243: Energy Efficiency - Large Buildings - Building Thermal Envelope
- NZS 4246: Energy Efficiency - Installing Bulk Thermal Insulation in Residential Buildings

Technical

NZBC Compliance: GreenStuf® thermal insulation when installed in accordance with the manufacturer's instructions will satisfy the 50 year durability clause NZBC B2.3.1 (a). GreenStuf® meets the relevant clauses of NZBC E3 Internal Moisture, F2 Hazardous Building Materials, and will contribute to meeting H1 Energy Efficiency.

Acoustic Performance: GreenStuf® insulation will assist sound reduction by reducing the resonating noise inside the construction cavity. Typical improvement in sound transmission loss through walls with the use of GreenStuf® R2.0 Wall insulation is an increase of 5-6 STC points.

Hazardous Building Materials: GreenStuf® is non-hazardous.

Durability: GreenStuf® has a 50 Year Durability Warranty.



Moisture: GreenStuf® is not affected by moisture. Exposure to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption by weight of less than 0.03%.

Non-Flammable: GreenStuf® is classified non-flammable.

Fire ratings:

ISO 9705: 1993

Classification: Group 1-S

Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

Issued 11th March 2013, BRANZ (FAR 4045)

AS1530.3

Ignitability Index (0-20) 0

Heat Evolved Index (0-10) 0

Spread of Flame Index (0-10) 0

Smoke Developed Index (0-10) 3

APL Report 98055

IEC 60695-11-5 (Downlight Fire Test Standard)

GreenStuf® has been tested and certified non-flammable and complies with the requirements of IEC 60695-11-5.

PRODUCT (R Value)		NOMINAL THICKNESS (mm)	PACK SIZE	PRODUCT WEIGHT (gsm)	DENSITY (kg/m ³)	m ² /PACK
R2.0 Wall Retrofit	✓	70mm	560mm x 1160mm x 10 pads per bale	3,600 gsm	51.4 kg/m ³	6.50m ²
R2.0 Wall	✓	90mm	560mm x 1160mm x 18 pads per bale	1,500 gsm	16.7 kg/m ³	11.69m ²
R2.0 Wall	✓	90mm	360mm x 1160mm x 20 pads per bale	1,500 gsm	16.7 kg/m ³	8.35m ²
R2.2 Wall	✓	90mm	560mm x 1160mm x 18 pads per bale	1,950 gsm	21.7 kg/m ³	11.69m ²
R2.2 Wall	✓	90mm	360mm x 1160mm x 18 pads per bale	1,950 gsm	21.7 kg/m ³	7.52m ²
R2.5 Wall	✓	90mm	560mm x 1160mm x 10 pads per bale	3,150 gsm	35.0 kg/m ³	6.50m ²
R2.5 Wall	✓	90mm	360mm x 1160mm x 12 pads per bale	3,150 gsm	35.0 kg/m ³	5.01m ²
R2.9 Ceiling	✓	175mm	430mm x 1220mm x 13 pads per bale	1,550 gsm	8.9 kg/m ³	6.82m ²
R3.2 Ceiling	✓	180mm	430mm x 1220mm x 13 pads per bale	1,700 gsm	9.4 kg/m ³	6.82m ²
R3.4 Ceiling	✓	190mm	430mm x 1220mm x 10 pads per bale	1,950 gsm	10.3 kg/m ³	5.25m ²

VOC Emission Safe:

VOC concentration: 0.01 mg/m³ (7 days).

GECA/GreenGuard Limit: 0.25 mg/m³ (7 days).

Cetec Pty Ltd (Report:RCV080408)

Non-Corrosive: GreenStuf® polyester is pH7.8 (pH7 is neutral)

Non-Toxic, Non-Allergenic, Non-Irritant: There are no known hazards with the use or handling of GreenStuf® polyester.

Vermin: GreenStuf® is naturally resistant to insect and vermin attack.

Installation: Autex Insulation recommends that all thermal and acoustic insulation be installed in accordance with the manufacturer's instructions (included on each GreenStuf® PADS pack) and NZS 4246 Energy Efficiency - Installing Bulk Insulation in Residential Buildings.

With a drained cavity wall construction and stud spacings greater than 450mm, NZBC E2/AS1, 9.1.8.5 Wall Framing behind Cavities, requires stud straps to prevent insulation bulging into the cavity. Straps must be run at 300mm centres over the wall underlay.

When retrofitting in exterior walls (without wall underlay) with direct-fixed claddings, use semi-rigid insulation that is at least 20mm thinner than the framing width (e.g. for walls with 90mm framing, the insulation shall be no thicker than 70mm).

MSDS: Material Safety Data Sheets (MSDS) are available on request from your Autex Representative or by visiting our website: www.autex.co.nz

Specification & Substitution: Autex specification documents are available through Masterspec® or can be downloaded from our website (www.autex.co.nz). Substitution of any products in NZBC compliant systems should not be accepted and we recommend this be made clear in all specification and tender documents.

ISO Standards: Autex is committed to Quality and Environmental best practice through our ISO 9001 & ISO 14001 certified Quality and Environmental Management Systems.

Take Back Programme: GreenStuf® is recyclable. Autex will gladly recycle used, uncontaminated GreenStuf® insulation to help keep it out of landfill. For more information on recycling GreenStuf® contact Autex on freephone 0800 428 839.

Packaging Recycling: GreenStuf® packaging is recyclable LDPE 4. Please refer to your local recycling centres for drop off and collection services.

Environmental: All GreenStuf® products are manufactured using 100% polyester fibre and contain a minimum of 45% previously recycled fibre (from PET plastic). GreenStuf® products are manufactured under Autex's Zero Waste Programme where all manufacturing waste is recycled back into the production process.

GreenStuf® products are Global GreenTag GreenRate Level A certified and can be used to contribute to Green Star NZ and HomeStar accreditation. GreenStuf® is also Declare certified to be Red-List Free and can be used in Living Building Challenge projects.

All product declarations are independently verified under our ISO 14001 Environmental Management System. For more information, please contact your Autex Account Manager, or visit our website www.greenstuf.co.nz

Declare.



GreenStuf® is manufactured in New Zealand by Autex Insulation, a division of Autex Industries Limited. Autex retains the right to change products and specifications without prior notice. If a specification is critical to end use situation please discuss your requirements with your Autex Representative.

GreenStuf® is a registered trademark of Autex Industries.

GS_NZ_DS_Thermal-Pads-Data-Sheet_OCT17_TC

AUTEX



Insulation

Autex Industries Ltd
 702 - 718 Rosebank Rd
 Private Bag 19988,
 Avondale 1746, Auckland
 New Zealand
 Phone +64 9 828 9179
 Fax +64 9 828 5810
 Freephone 0800 428 839
www.autex.co.nz

ISO 9001 AND ISO 14001 CERTIFIED