



UNDERLAY STRAP

For support of underlays - roof and wall

Thermakraft underlay straps are suitable for supporting non self-support roof underlays and restricting bellowing of wall underlays in drained cavities. Both are supplied in handy dispenser packs.

ADVANTAGES

Stud Strap

Polypropylene woven and coated

- » High strength.
- » Ideal for large wall applications.
- » Easy one hand dispenser.



WIDTH (MM)	LENGTH (M)	COLOUR	
25	250	Black	

Thermastrap 201 Polythene embossed strap

- » High tensile strength.» Convenient
- dispensing box.Tough construction.

the second se	-	Thermakra		
Ideal for large walf applications • Eas to ab hardy disperse • For our wind Thematian and only a • Designed to restrict insulation beforeing into dising davites • Use as support for on-self-approximation before • Use as support for on-self-approximation and only and • Use as support for on-self-approximation and only approximation and • Use as support for on-self-approximation and only approximation and • Use as support for on-self-approximation and only approximation and • Use as support for on-self-approximation and only approximation and • Use as support for on-self-approximation and only approximation and • Use as support for on-self-approximation approximation and only approximation and • Use as support for on-self-approximation approximation approximat	12	imal.		I ENIVERSI NAT
Easy to use hanky dispenser For use with all Thermatural underlaw Generative struct insulation beforeing into chained cavities Use as support for non-self-supporting root underlays	1			
 Not meas, no Pass High strength strap embessed 400 micron thickness 			SED STRAP	

WIDTH (MM)	LENGTH (M)	COLOUR
19	300	Blue





