

Cabot's Aquadeck

NZDW1378

Part A	567-Line
---------------	----------



Description
Cabot's Aquadeck ia a highly durable, low odour, water based decking oil which delivers a long lasting, beautiful result.

Features
<ul style="list-style-type: none"> Water based. UV shielding pigments. Superior oil enriched formula.

Benefits
<ul style="list-style-type: none"> Easy to use and quick drying. Provides UV protection. Tough, long wearing finish.

Uses
Exterior timber decking, patios and porches.

Performance Guide			
Weather	Formulated for exterior use.	Salt	Good.
Heat Resistance	Up to 70C. Higher temperatures will cause the film to soften.	Water	Good water resistance.
Solvent	Sensitive to aromatic solvents and alcohols.	Abrasion	Moderate abrasion resistance.
Acid	Fair.	Alkali	Fair.

Typical Properties																											
Gloss Level	Matt	Thinner	Do not thin.																								
Colour	Kwila & Traditional.	Components	1																								
Number Of Coats	2	Toxicity	Lead free. dry film is non-toxic.																								
V.O.C. Level	37 g/L	Touch Dry	1 Hour																								
Clean Up	 Water																										
Application Method	  Brush Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">16.4</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td style="text-align: center;">Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">84</td> </tr> <tr> <td style="text-align: center;">Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">13.7</td> </tr> <tr> <td style="text-align: center;">Recoat Time (min)</td> <td style="text-align: center;">2 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td style="text-align: center;">Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">12</td> </tr> </table>			Solids By Volume	16.4				Min	Max	Recommended	Wet Film Per Coat (microns)			84	Dry Film Per Coat (microns)			13.7	Recoat Time (min)	2 Hours	Indefinite		Theoretical Spread Rate (m ² /L)			12
Solids By Volume	16.4																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			84																								
Dry Film Per Coat (microns)			13.7																								
Recoat Time (min)	2 Hours	Indefinite																									
Theoretical Spread Rate (m ² /L)			12																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> NEW & FRESHLY SANDED TIMBER Wash with Cabot's Deck Clean to remove dirt, mildew, mould, oil, wax and tannins. Allow to dry, then coat immediately. Heavy deposits of oil or wax should be removed first with mineral turpentine. PREVIOUSLY OILED, STAINED OR WEATHERED TIMBER If badly weathered, sand back to fresh timber before coating. If previously coated with a water-based decking oil, simply wash with Cabot's Deck Clean before recoating. If previously coated with a conventional decking oil, first ensure that it has lost its water repellency, then wash as above before coating. If previously coated with a decking stain, wash with Cabot's Deck Clean, sand lightly, remove sanding dust and apply Cabot's Aquadeck.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush or pad applicator. Stir thoroughly with a broad paddle before and during use. Apply two liberal coats using a quality brush or pad applicator. Apply along the length of the board, including exposed edges and end grain. After several minutes, remove excess with brush or pad applicator.

Health And Safety			
MSDS Number	21245		
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000021245.pdf		
Health Effects	Splashes to eyes will cause irritation. Prolonged skin contact with liquid is harmful and inhalation of vapour or spray mists may produce headaches.	Flammability	This product is non-flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Disposal	Do not dispose down the drain. Refer to your local council for correct disposal procedures.
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
Do not apply if temperature is below 10C or likely to fall below that during the drying period. Do not apply to hot surfaces or those in direct sunlight, or in temperatures above 30C. Do not apply if rain or dew is likely within 4 hours of application.

Transport And Storage			
Pack A	567-Line		
Size	1L 4L 10L	Weight	1.2Kg 6Kg 11Kg
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118