

Inseal® 3259 Single Sided Foam Tape DATA SHEET



Product Description

- Foam type: Medium density, closed cell PVC foam
- Application types: Air/dust and water seals
- Adhesive: Pressure sensitive acrylic adhesive on one side of tape
- Colour: Black
- Available thicknesses: 1.5, 3, 4.5, 6, 7.5, 9, 10.5 & 12mm

Applications

- Air ventilation filters, separating metal to inhibit corrosion, anti-slip pads, sealant for windows etc

Technical Specifications

- Compression required to achieve seal: 30%
- Force to Compress by 30%: 0.30 kg/cm²
- Compression Deflection: 0.23 kg/cm²
- Shore Hardness (OO) scale: 30
- U.V Resistance: Very good
- Service Temperature: -30°C to +70°C
- Shelf life: 12 months

Features and Benefits

- BRANZ appraised (appraisal 442, 2005) for use behind joints in exterior sheet claddings to provide protection against possible water penetration. For more information view the appraisal: <http://www.branz.co.nz/Appraisal/442>
- Fire rated to DIN 4102 part 1, B2

Storage Details

- Life expectancy will vary with temperature and humidity
- Low temperatures may increase the risk of condensation, which will reduce the tack of the product

IMPORTANT – PLEASE READ

PRODUCT USE – All statements, technical information and recommendations contained in this document are provided for general information purposes only about the products referred to herein (Products). They are based upon tests or experience that Henkel New Zealand Limited (Henkel) believes are reliable. However, many factors beyond Henkel's control affect the use and performance of a Product in a particular application, including the conditions under which a Product is stored, handled and used and the time and environmental conditions in which a Product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is the user's responsibility to evaluate each Product to determine whether it is fit for a particular purpose and suitable for the user's method of application, as well as, to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of a Product. It is also the user's responsibility to check that the data sheet they have is the latest version that has been published by Henkel in connection with the Products.

NO WARRANTIES – In light of the foregoing, to the maximum extent permitted by law, Henkel MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE in connection with any Product. In addition, Henkel is not liable for representations made by suppliers or retailers about the Products.

LIMITATION OF REMEDIES AND LIABILITY – In any event (and without limiting the foregoing), THE EXCLUSIVE REMEDY, AT HENKEL'S SOLE DISCRETION, SHALL BE TO REFUND THE PURCHASE PRICE OF THE DEFECTIVE PRODUCT OR TO SUPPLY REPLACEMENT PRODUCT. Henkel shall not otherwise be liable for loss or damages, whether direct, indirect, special, or consequential, regardless of the legal theory asserted, including negligence.

Henkel Consumer Adhesives

2 Allens Road, East Tamaki, Auckland 2013

Phone: 0508 735 568

Website: www.sellotape.co.nz

Quality for Professionals

