



maxbond ORIGINAL CONSTRUCTION ADHESIVE

Description

maxbond Original Construction Adhesive is ideal for bonding timber and most common construction materials including particle board, MDF board, brick, concrete, gypsum board, galvanized metal and aluminum. maxbond Original Construction Adhesive is a synthetic rubber based adhesive designed primarily for installation of flooring and wall panels. maxbond Original Construction Adhesive can be used in many general household applications.

Benefits

- One part - no mixing.
- Paintable with most surface coatings.
- Reduces squeaking associated with nail ride in floors.
- Complies with AS 2329 – 1999 requirements.
- Repositionable for up to 20 minutes after application.
- Reduces number of mechanical fasteners required to install floors or walls.
- Water resistant - will not break down in intermittent contact with water (e.g. rain).
- Natural wood colour - blends in.
- High bond strength.

Uses

- Installing particle board, fiber cement, plasterboard, plywood and strip flooring to joists

- Bonding fiber cement sheet, plaster board and wall paneling to wooden and metal studs High bond strength and heat resistance
- Skirting boards, architraves and trims to walls
- mirrors to walls (not overhead)
- replacing loose tiles on walls (not recommended for floor tiles)

Compatible Substrates

Concrete	Fiberglass
Cement sheeting	Plywood
Metal	Particleboard
Plasterboard	Ceramic
Timber	Masonry
Brick	

Coverage

300g cartridge will give 14 lineal meters of a 5mm bead, or 2 sheets of 1.2 x 2.4 meter panel.

When trowelled out

- 2.5mm trowel ~ 1.4m²/litre approx.
- 3.0mm ~ 1.2m²/litre approx.
- 4.0mm ~ 0.6m²/litre approx.

Surface Preparation

Only apply to surfaces that are clean, dry, sound and free of dust oil or contamination. Clean metal with mineral turps* or white spirits*. Adhesion to metals can be further improved by light sanding.

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 2225588





Application

Cut tip off cartridge, screw on nozzle and load into cartridge gun. Cut nozzle tip to a 5mm diameter hole (or desired size). Squeeze trigger and apply.

Performance Summary

Skimming time	1-5 minutes.
Repositioning time	< 20 minutes.
Full cure	Seven days, depending on conditions.
Sag Resistance (AS 2329 - 1999, Appendix A)	< 6 mm
Transfer (AS 2329 - 1999, Appendix B)	> 75 % after 15 minutes open time.
Aging (AS 2329 - 1999, Appendix C)	No chipping or cracking after 500 hours at 70°C.
Initial Bond Strength (AS 2329 - 1999, Appendix D)	>200kPa
Tensile Bond Strength (AS 2329 - 1999, Appendix E)	>1MPa Initial, >0.8MPa aged.
Static Load (AS 2329 - 1999, Appendix G)	PASS (No movement)

Flooring and Wall Panels

Apply a wavy 5mm diameter. Bead to each joist, batten or stud. Where sheets will butt together, apply 5mm beads along both edges of that joist, batten or stud so each sheet edge will be on a glue line.

Floors

Fit sheet to joist within 15 minutes. Stagger end-joins leaving 1.5mm gaps between them to allow for expansion. Nail or screw sheets to joists at 150mm centers around the perimeter and 300mm centers through the middle, or per manufacturers instructions. Use putty knife to remove any adhesive squeezed out between the sheets.

Walls

Fit panel to stud within 15 minutes and press firmly into position. To speed up the bonding, tilt panel back for a few minutes to allow solvent to escape. Refit panel making sure glue line matches up. Press firmly together. Nail or screw panels as for floors per manufacturers instructions. If not nailing or screwing, brace panel for at least 24 hours, until set. When bonding a sheet or panel to a large, flat surface, apply full length 5mm diameter. Beads every 30-40cm. Press into position and brace until set.

Concrete Slab floors

Slab on ground or below ground

Must have an effective water vapour barrier. Concrete must have been poured at least 60 days prior to application and have moisture content below 3%. Concrete must be free of any surface water, curing compound residues, loose or weak surface concrete. Patch all holes with a strong bonding compound.

Above ground concrete floors

Must be at least 45 days old, free of surface dampness and curing compound residues,

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 22225588



loose or weak concrete. Patch all holes with a strong bonding compound.

Application

Apply maxbond Original Construction Adhesive and trowel out with a 2.5mm, 3mm, or 4mm V notched trowel depending on surface roughness of floor. Only apply as much maxbond Original Construction Adhesive as can be covered in 10 minutes by flooring.

Mirrors

Use maxbond Original Construction Adhesive for mirrors on walls only, not for mirrors on ceilings. Apply wavy 5mm diameter beads, parallel about 20cm apart. Do not apply across the top or bottom of the mirror as solvent needs a way out, do not apply as a blob. Mechanical fastening is recommended. Use 'wall panel tilt method' to speed up setting and reduce solvent build up. Brace until set. Do not fix mirrors if temperature is over 30 degrees centigrade. maxbond Original Construction Adhesive is suitable for bonding standard silvered backed mirrors only, not vinyl or safety backed mirrors.

Polystyrene Foam Panels

When installing Polystyrene foam panels using maxbond Original Construction Adhesive the adhesive must be applied as parallel beads, each no more than 5 mm in diameter. Once Maxbond is applied the polystyrene must be brought into contact with the other substrate and the maxbond Original Construction Adhesive beads completely spread, before again separating the substrates. Then allow solvent from maxbond Original Construction Adhesive to

flash off for approx 1 to 2 minutes before bring the substrates into final contact. Do not apply maxbond Original Construction Adhesive onto Polystyrene foam as a blob. The surface to which the panels are to be fixed must not exceed 30°C. Failure to comply with these instructions will result in damage to the Polystyrene foam panel. For this reason, exterior installation of Polystyrene foam components using maxbond Original Construction Adhesive is not recommended. In these cases consider maxbond Fast Grip.

Cure Time

maxbond Original Construction Adhesive forms a thin skin in 2 - 5 minutes depending on air temperature. The skin can be broken simply by pressing the floor or wall board firmly onto the adhesive with a slight twisting movement.

90% cure in three to five days.

100 % cure in seven days.

Cure rate will depend on temperature, porosity of substrates and ventilation.

Service Temperature

maxbond Original Construction Adhesive will maintain a bond in situations where the temperature is continually between 0°C and 40°C. maxbond Original Construction Adhesive will withstand temperatures up to 80°C where there is a light load and if the exposure to this temperature is not prolonged.

Painting

maxbond Original Construction Adhesive may be painted after it has cured.

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 22225588





Clean Up

Wet: mineral turpentine*.
Dry: scraper or sandpaper.

Limitations

- Do not use maxbond Original Construction Adhesive where temperatures will exceed 80°C.
- maxbond Original Construction Adhesive is not suitable for immersion.
- maxbond Original Construction Adhesive can be used in exterior applications, but must not be exposed to prolonged direct Sunlight.
- Do not apply at temperatures below 5°C.

Safety Information

maxbond Original Construction Adhesive is classified as hazardous according to criteria of Worksafe Australia. maxbond Original Construction Adhesive is highly flammable. Keep away from sources of ignition. Do not inhale vapour. Ensure good ventilation in area of use. maxbond Original Construction Adhesive is a Dangerous Goods Class 3.

A Material Safety Data Sheet is available from the H.B. Fuller representative your state, HB Fuller Australia customer service, or downloadable from the HB Fuller web site, www.hbfuller.com.au

Disclaimer

This technical data sheet summarises at the date of issue to the best technical knowledge of HB Fuller Australia. Since HB Fuller Australia cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review

this technical data sheet in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request

Shelf Life

Use product prior to the best before date printed on the bottom of the cartridge.

Version 2
TDS Date: 29/11/2017

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 2225588

