

Code	Description	Size	Colour
19391	Gorilla 696 Surface Activator	100ml	Transparent
19389	Gorilla 696 Surface Activator	500ml	Transparent
19392	Gorilla 696 Surface Activator	5Lt	Transparent

1. Description

Gorilla 696 Surface Activator is a cleaner, degreaser and Primer. Surface Activator will activate non porous surfaces such as plastics, coatings and metal for improved adhesion of sealants based on silicone, polyurethane and MS Polymer.

2. Characteristics

- Liquid, easy to use
- To be used as cleaner and Primer on non Porous Surfaces
- Suitable for silicone, polyurethane and hybrid sealants

3. Technical Data

Base:	Solvents and special activating agents
Consistency:	Liquid
Specific Gravity:	0.78
Flashpoint:	130C
VOC (%):	86%
VOC (g/litre):	860

4. Applications

Preparation of some plastics, powder coatings and other non porous surfaces before bonding and sealing.

5. Packaging

100ml, 500ml, 5Lt

6. Shelf Life

12 months in an unopened packaging on a dry and cool storage place at temperatures between +5°C and +25°C.

7. Application Instructions

Apply Surface Activator with a clean cloth. By doing so the surface is cleaned, degreased and activated for the application of the sealant.
 Replace cloth regularly when dirty
 Leave to evaporate for 5 minutes
 Apply sealant/adhesive immediately after evaporation.

Soudal recommends a preliminary compatibility tests to ensure that you get the desired end result.

8. Precautions

Please note that the formulation may inadvertently affect the gloss levels of any painted/powder-coated surfaces. Holdfast NZ Ltd recommends a preliminary test to be carried out to ensure that you achieve the desired result.

9. Health and Safety Recommendation

- Apply the usual industrial hygiene

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email sales@soudal.co.nz.***

Last Updated: 29 July 2019

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	Fax: (07) 847 0324
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz