

Rear dust exhaust port

exhausts sawdust backward only, preventing it from scattering around to provide comfortable operation.

2 Single action lever

for quick adjustment of cutting depth and bevel angle.

3 Flat Motor Housing Design

Increases stability when changing blades.








Comparison of Efficiency (Cutting speed)

Note: Numbers in the chart below is relative values when the capacities of Predecessor Model is indexed at 100.

Test material: Melapi (60mm thick x 300mm long)
Bevel angle: 0 degree



Circular Saw	HS7600 185mm (7-1/4")		303
Double Insulation	Continuous rating input	1,200W	
Lang Dust Collecting	Max cutting capacity	at 0 degrees :	
		64mm (2-1/2")	
		at 45 degrees : 42mm (1-5/8")	
	Blade diameter	185mm (7-1/4")	
	No load speed (rpm)	5,200	
	Dimensions	309x234x255	
	(LxWxH)	(12-1/8"x9-1/4"x10")	
	Net weight	3.9kg (8.6lbs)	
	Power supply cord	2.5m (8.2ft)	
	Standard Equipment :		
	Carbide-tipped saw blade, Hex wrench, Rip fence (guide rule)		
		weight according to EPTA-Pro	cedure

weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

