

LS1219L 305mm Slide Compound Mitre Saw



- Unique 2-Steel Rail Sliding System Design Allows Operation Flush Against a Wall
- Increased capacity for up to 203 mm (8") crown moulding (vertically nested), 171 mm baseboard (vertical), and 382 mm crosscuts at 90°
- Dual dust collection ports provide excellent dust extraction performance
- In-front bevel lock for convenient operation
- Large turn base supports workpiece securely for increased stability
- Integrated guide fences for increased rigidity and high cutting accuracy
- Single sliding system enables smooth operation to produce superior cuts
- Mitres 0-60° left and right; bevels 0-48° left and right
- Positive mitre stops at: 0°, 15°, 22.5°, 31.6°, 45°, and 60° left or right
- Increased sliding durability of safety cover
- Slide lock for locking the sliding movement of the carriage
- Holders are provided on both sides of the tool to hold long workpieces horizontally
- Ergonomic rubberised horizontal D-handle design for better fit and added comfort
- Electric brake for maximum productivity and increased operator safety
- Soft start suppresses start-up reaction for smooth start-ups and

longer gear life

- Electronic speed control maintains constant speed under load for smoother, higher quality cutting
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort and easier operation
- Lock-off (2 stage) safety switch for increased operator safety. Incorporates Deep eXact cutting Technology (DXT) achieved by our consistent pursuit of cutting larger size workpiece but with higher accuracy. Dust bag for a cleaner work environment. On-tool hex wrench for fast and easy blade changes and keeping it from lost. Externally accessible brushes for easy replacement. Double insulated

Specifications

Blade diameter	305mm
Max cutting capacities	
- at 90°	92 x 382 mm
Bevel angle	48° L / 48° R
No load speed	3,200rpm
Net weight	29.5kg
Continuous rating input	1,800W
Power supply cord	2.5m

All product and accessory specifications are subject to change without notice.

Available options

LS1219L

