
Product data sheet





Combi Laser

GCL 2-50 CG



Supreme visibility connected with smart functions

The most important data

Working range with receiver	50 m
Working range	20 m
Accuracy	± 0.3 mm/m

Order number 0 601 066 H80

> More product information

Technical data

Technical data

Laser diode	500 - 540 nm, < 10 mW, 630 - 650 nm, < 1mW
Operating temperature	-10 - 50°C
Storage temperature	-20 - 70°C
Laser class	2
Working range	20 m
Working range with receiver	50 m
Accuracy	± 0.3 mm/m
Working range of laser points, max.	10 m (top), 10 m (bottom)
Self-levelling range	± 4°
Dust and splash protection	IP 54
Operating time (max.)	10 h (Li-Ion) and 4 h (4 x AA) in cross-line and point operation, 13 h (Li-Ion) and 6 h (4 x AA) in cross-line operation, 15 h (Li-Ion) and 12 h (4 x AA) in line operation, 60 h (Li-Ion) and 32 h (4 x AA) in point operation
Tripod thread	1/4"
Weight, approx.	0.6 kg
Colour of laser line	green

Projection	2 lines / 2 points
Plumb point accuracy	± 0.7 mm/m
Compatible laser receivers	LR 7

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Bright green horizontal and vertical laser lines and two centred plumb points offer optimal visibility
- Bluetooth®-connection paired with Levelling Remote App offers remote-control adjustment of the tool via a smartphone
- Dual Power Source allows for the use of 12 V Li-ion battery or standard alkaline batteries



























