
# Product data sheet





Line Laser

## GLL 3-80 CG



Green supreme visibility in 3 x 360°. Simply connected.

### The most important data

Working range with receiver	120 m
Working range	30 m
Accuracy	± 0.2 mm/m

**Order number** 0 601 063 U80

## > More product information

## Technical data

#### Technical data

recrimear data	
Laser diode	500 – 540 nm, < 10 mW
Operating temperature	-10 - 40°C
Storage temperature	-20 - 70°C
Laser class	2
Working range	30 m
Working range with receiver	120 m
Working range without receiver	30 m
Accuracy	± 0.2 mm/m
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 54
Power supply	12 V Li-lon battery, 4 x 1.5 V LR6 (AA)
Operating time (max.)	6 h (Li-Ion) and 4 h (4 x AA) in 3-Iine mode
Tripod thread	1/4", 5/8"
Weight, approx.	0.9 kg
Colour of laser line	green
Projection	3 x 360° line
Compatible laser receivers	LR 7

# Invented for life

# Product data sheet

## Power tools for trade & industry

# Advantages:

- Up to four times better visibility due to the green laser lines
- Bluetooth® connection to your smartphone for remote control use and contactless adjustment of the tool
- High work efficiency due to 3 x 360° lines: Simultaneous performance of horizontal and vertical levelling applications in the entire room with only one tool



























