

[Home](#)[Products ▾](#)[Videos](#)[Downloads](#)[Contact Us](#)[About](#)[Search](#)

[Bordo](#) ⇨ [Drills](#) ⇨ [Specialist](#) ⇨ [Long Series HSS](#) ⇨ [Metric Bulk](#)

6mm HSS Long Series Drill

Part No.	2501-6.00
Diameter (mm)	6
Flute Length (mm)	95
Overall Length (mm)	156
Pack Quantity	1
Spindle Speed Stainless Steel RPM	637
Spindle Speed Tool Steel RPM	956
Spindle Speed Cast Iron RPM	1274
Spindle Speed Malleable Iron RPM	1433
Spindle Speed Med. Carbon Steel RPM	1593
Spindle Speed Free Cutting Steel RPM	2283
Spindle Speed Aluminium/Brass RPM	3238
Spindle Speed Wood/Plastic RPM	4831
Feed per revolution mm	0.13
Barcode	9326518052760



BLACK FINISH (also called blue finish) A black finish is achieved by steam tempering, a thermal process resulting in a porous tool coating. This surface helps to keep lubricant on the tool, particularly important on the cutting edges, thus reducing friction and cold welding. The result is increased tool life. Black finish tools are generally recommended for ferrous applications where the oxide layer aids chip flow and heat dissipation.