

## ECHO 3 FUNCTION RAIL SHOWER MKII



**CONSTRUCTION:** Metal rail

**CLASSIFICATION:** Suitable for mains pressure only

**INLET CONNECTIONS:** 1/2" BSP

**WORKING PRESSURE:** 150 - 500kPa

**DIMENSIONS FOR FITTING:** Hole spacing from 420mm to 620mm

**OPERATING TEMPERATURE:** 5 °C - 70 °C

**WATER FLOW RATE:** 8.0 l/m

- 3 spray function showerhead
- Adjustable wall brackets for retrofit installation
- Clear plastic soapdish and double wound metal hose included
- 3 star WELS rated on mains pressure
- 5 year warranty

E8502

Chrome

<http://www.methven.com/nz>

## ECHO SINGLE FUNCTION RAIL SHOWER MKII



**CONSTRUCTION:** Metal rail

**CLASSIFICATION:** Suitable for **all pressures**

**INLET CONNECTIONS:** 1/2" BSP

**WORKING PRESSURE:** 35 - 500kPa

**DIMENSIONS FOR FITTING:** Hole spacing from 420mm to 620mm

**OPERATING TEMPERATURE:** 5 °C - 70 °C

**WATER FLOW RATE:** 8.5 l/m on mains pressure - 6.0 l/m on low pressure

- Low maintenance single function shower
- Adjustable wall brackets for retrofit installation
- Clear plastic soapdish and double wound metal hose included
- 3 star WELS rated on mains and low pressure
- 5 year warranty

E9502

Chrome

<http://www.methven.com/nz>