

Code	Description	Size	Colour
0129.2	Gorilla Plumbers Putty	250gr	White
01293	Gorilla Plumbers Putty	500gr	White
01296	Gorilla Plumbers Putty	150gr	White

1. Description

Gorilla Plumbers Putty is a ready to use paste which can be kneaded into the required form for many plumbing applications.

2. Characteristics

- Excellent adhesion
- Remains elastic
- High bonding strength
- Withstands water, acids and alkalis

3. Technical Data

Base:	Polybutene and mineral oils
Consistency:	stable, kneadable paste
Curing:	does not dry, remains plastic
Density:	1.9
Temperature Range:	-20°C tot + 120°C
Adhesion:	Self-adhesive

4. Applications

Many different plumbing applications, sealing of metals.

Installation of sanitary equipment (toilets and sinks) on floors.

Installation of taps onto sinks.

5. Packaging

Plastic container 150gr, 250gr and 500gr (net content)

6. Shelf Life

2 years in unopened packaging in a cool and dry storage areas at temperatures between +5°C and 25°C.

7. Application Instructions

Surfaces

Preparation: Ensure surface is clean, dry and free of dust and grease. A good surface preparation will ensure better adhesion.

Application

Method: Apply between -1°C and 30°C, knead the required quantity and apply onto the substrate.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene.
- Pre-testing for adhesion is intended to eliminate potential field problems. This testing will aid in determining the proper surface preparation method.
- For more detailed information, please refer to the SDS.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email sales@soudal.co.nz.***

Last Updated: 25 July 2019