

UNISEAL®

- Long Life
- Easy to install
- Replaces most bolt-on flanges
- Can withstand suction, acids and oils, sewerage and waste, heat and cold
- 3-12mm Wall thickness

CODE	SIZE	PIPE ID	PIPE OD	HOLESAW SIZE
U018		3/16"	6mm	10.0mm
U025		1/4"	10mm	12.7mm
U038	10	3/8"	17mm	25.4mm
U050	15	1/2"	21mm	31.7mm
U075	20	3/4"	27mm	31.7mm
U100	25	1"	33mm	44.4mm
U125	32	1 1/4"	42mm	50.8mm
U150	40	1 1/2"	48mm	63.5mm
U200	50	2"	60mm	76.2mm
U300	80	3"	89mm	101.6mm
U400	100	4"	114mm	127.0mm
U400-35		4"	110mm	127.0mm
U600		6"	168mm	178.0mm
U600-35	SW	6"	160mm	178.0mm

Metric Hole Tolerance +2mm

Installation Instructions:

1. Cut hole to the Holesaw size indicated for the UNISEAL® you are using. (see above).
Example: 3" UNISEAL® = 4" Hole (Holesaw).
2. Ensure that the hole is clean cut with sharp edges. Irregularities could cause poor seating and leakage.
3. Insert the UNISEAL® into the hole with the wide side facing the pipe to be inserted.
4. Make certain that the pipe end to be inserted is clean cut. File the edges so that there are no sharp points to cut UNISEAL®.
5. Using Detergent, lubricate the outside of the pipe end to be inserted, then push the pipe through the UNISEAL® from the large flange side. The detergent will be squeezed off as the pipe passes through the UNISEAL®. The co-efficient of friction of the rubber holds the pipe tightly in place.

