



Producer Statement and Maintenance Guide

Promax

LIQUID MANAGEMENT SOLUTIONS



AS/NZS 4766 BMP No 657394
Australian/New Zealand Standards

Date: 01.04.2018

Product Code: PMXUT050001.2

Product Description: Promax Underground Tank - 5,000 litres

Product Specifications: 1280mm OD x 5000mm Long with 600mm ID Manhole
1730mm Total Height including riser and sump
Complies with AS/NZS 4020, AS/NZS 2070 Potable Water Standards. AS/NZS 2566:1-1998 with a load rating of 28kpa for vehicular traffic

Product Uses: Potable Water Storage
Retention/Detention Stormwater Management
Waste Storage

Product Warranty: 5 years

Producer Statement: In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions

Promax plastics manufactures these tanks to a high standard of quality. This Promax Underground Tank may be used for retention/detention and/or the storage of potable water, storm water and waste water complying with the appropriate NZ Standards.

The heavy duty corrugated profile of these tanks have been tested and proven over many years in specific underground applications to a load rating of 28kpa for vehicular traffic.

Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Underground Installation Guide, they will perform as stated throughout their intended life.

Maintenance Guide:	Description	Action	Frequency
	Tank Stability	Tank must remain level, foundation must not become eroded or the tank lift	Monthly
	Tank Lid	Remains securely fitted	Bi-monthly
	Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-monthly
	Pump	Check Pump, if fitted, for inlet screen blockages	Bi-monthly
	Sediment Build Up	Remains lower than base outlet - if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

Please note: Entry into this tank is at owners risk.

Authorised By: Promax Engineered Plastics Limited
PO Box 749, Kerikeri 0245,
New Zealand