Producer Statement and Maintenance Guide



Date: 01.04.2018

Product Code: PMXSL03000

Product Description: Promax Slimline Water Tank - 3,000 litres

AS/NZS 4766 BMP No 657394

Product Specifications: 760mm wide x 2400mm long x 2120mm high

25mm BSP threaded Base Outlet, Weight 125kg

Complies with AS/NZS 4020, AS/NZS 2070 (INT) Potable Water Standards. Certified to AS/NZS 4766:2006 Water and

Chemical Tank Standard.

Product Uses: Potable Water Storage

Retention/Detention Stormwater Management

Product Warranty: 5 years - Life expectancy of 30 years under normal operation conditions

Producer Statement: In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid

Storage and Handling Solutions

Promax plastics manufactures these tanks to a high standard of quality. This Promax Underground Tank may be used for retention/detention and/or the storage of potable water, storm water, and waste water complying with the appropriate NZ Standards.

Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guide, they will perform as stated throughout their intended life.

Maintenance Guide:	Description Tank Stability	Action Tank must remain level, foundation must not become eroded or the tank lift	Frequency Monthly
	Tank Lid	Remains securely fitted	Bi-monthly
	Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-monthly
	Pump	Check Pump, if fitted, for inlet screen blockages	Bi-monthly
	Sediment Build Up	Remains lower than base outlet - if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

Please note: Entry into this tank is at owners risk.

Authorised By:

Promax Engineered Plastics Limited PO Box 749, Kerikeri 0245, New Zealand