

# CORDLESS PRO300 Auto-Feed Screw Driving System

Decking | Subfloor | Underlay | Cladding | Sheathing



The wait is over! Quik Drive is now **CORDLESS**. Save time and money with maximum freedom, high torque and consistent performance.

**360°**

**360°**

**Efficient**  
Quick loading yellow strip Quik Drive screw, allow for faster installation, less waste and jamming.

**Ergonomic**  
Compact and light weight, used from a standing position, results in less stress on back, shoulders and knees, with no trip hazards.

**Versatile**  
Quick breakdown for closeup work.

**Precise**  
Quick release countersink adjustment for consistent screw depth.

Allows for decking clips, for uniform installation of decking screws, without having to flick a chalk line (sold separately).

Built-in wrench for quick and easy replacement of bits.

The Cordless PRO300 system is ideal for, but not limited to, underlay, subfloor, sheathing and decking applications. Designed to drive 40 – 75 mm (8 – 12 gauge) screws, the PRO300 is a truly flexible tool to cater for a wide range of applications. Incorporating a precision countersink adjustment that produces consistent screw depth, combined with the auto-feed mechanism delivers fast, hassle-free driving on the jobsite.




## PRO300SG2DC2KA

- 1x Quik-Drive® PRO300 **Attachment**
- 1x Quik-Drive® G2 **Extension**
- 1x DeWalt® DCF622N **Screwgun** fitted with DWA3G2 adaptor\*
- 2x 18V XR 5.0Ah **Batteries**
- 1x XR Multi-Voltage **Charger**
- 1x Rugged **Toolbox**



## PRO300SG2DC2KA-S


- 1x Quik-Drive® PRO300 **Attachment**
- 1x Quik-Drive® G2 **Extension**
- 1x DeWalt® DCF622N **Screwgun** (Skin only) fitted with DWA3G2 adaptor\*
- 1x Rugged **Toolbox**



Drives Quik Drive collated fasteners

Length  
**40 – 75 mm**

Diameter (Gauge)  
**4.2 – 5.5 mm**  
(8 – 12 g)



Find handy **Quik Drive** videos on our channel

\*DeWalt® DCF622N screwgun has been modified to work with Quik Drive Screw Driving Systems. Not intended to be used as a regular screwgun.

# Screws available for the PRO300 System

Driver bits supplied with every box of screws • All genuine Quik Drive screws come in strips of 30 screws

## Deck-Drive™ Premium Decking Screws

### Deck-Drive™ DSV SOFTWOOD Screw

Rimmed flat-head with nibs, coarse thread, sharp point, Quik Guard® (Class 3) coating, T-25 6-lobe drive

<b>DSVT2S:</b>	10g x 50mm
<b>DSVT212S:</b>	10g x 65mm
<b>DSVT3S:</b>	10g x 75mm



- Designed to withstand the swelling and shrinkage that is common with softwood timber decking.



### Deck-Drive™ DHW HARDWOOD Screw

Compact head, coarse thread, winged, hardwood drill point, 305 stainless steel, #2 square drive

<b>SSDHW60SA:</b>	10g x 60mm
-------------------	------------



- Wings on the shaft counter-bore hard timber to allow the head to countersink for clean look



### Deck-Drive™ DHSD HARDWOOD Screw

Raised countersinking head, coarse thread, hardwood drill point, 305 stainless steel, #2 square drive

<b>SSDHS50S:</b>	12g x 50mm
<b>SSDHS60S:</b>	12g x 60mm



- Penetrates hardwood products with ease
- Unique drill point reduces splitting without pre-drilling



### Deck-Drive™ DSD HARDWOOD Screw

Rimmed flat-head with nibs, coarse thread, hardwood drill point, 316 stainless steel, T-25 6-lobe drive

<b>SSDSD50SA:</b>	12g x 50mm
<b>SSDSD65SA:</b>	12g x 65mm



- Low torque design for fast and easy driving.
- Broad head provides a greater clamping force and decorative finish.



### Deck-Drive™ BFHSD BI-METAL Screw

Ribbed flat head, 16 TPI, #2 drill point with wings, 316 stainless steel bi-metal, #2 square drive

<b>SSBFHSD2SA:</b>	10g x 50mm
--------------------	------------



- Zinc coated to prevent dissimilar metal reaction
- Suitable for 1.2mm – 2.4mm steel thickness



## Into Steel

### CBSD Cement Sheet Screw

Ribbed flat head, 18TPI, #2 drill point with wings, Class 3 galvanised, #2 undersize square drive

<b>CBSDG158SA:</b>	8g x 42mm
<b>CBSDGL158SA:</b>	10g x 42mm
<b>CBSDGL214SA:</b>	10g x 55mm
<b>CBSDGL3SA:</b>	10g x 75mm

- Engineered to fasten sheet flooring and timber to steel framing. (0.8 – 2.4mm 8g, 1.2 – 3mm 10g)



Look for the yellow strip. Your guarantee of quality and performance from **Genuine Quik Drive Fasteners.**

## Into Timber

### SSWSC Timber Screw

Flat head with nibs, coarse thread, type 17 point, 305 stainless steel, #3 square drive

<b>SSWSC134BS:</b>	8g x 45mm
<b>SSWSC2BSA10:</b>	10g x 50mm

- High corrosion resistance
- Type 17 point for easier driving



### WSNTLG Timber Screw

Flat head with nibs, twin lead thread, sharp point, Class 3 galvanised, #3 undersize square drive

<b>WSNTLG2SA:</b>	8g x 50mm
-------------------	-----------

- Twin Lead thread for faster driving and superior holding power compare to 3.75mm nails



### Strong-Drive™ WSV SUBFLOOR Screw

Rimmed flat head with nibs, aggressive variable thread, sharp point, Yellow zinc, T-25 6-lobe drive

<b>WSV50SA:</b>	10g x 50mm	(Complies with AS1860.2)
<b>WSV3S:</b>	10g x 75mm	(Complies with AS1860.2)

- The WSV tip and thread pattern provide easy starts and up to 25% less torque<sup>1</sup> – which leads to 20% faster driving.<sup>2</sup>

1. Test data shows the Strong-Drive® WSV Subfloor screw requires up to 25% less driving torque in single-material LVL.
2. The WSV thread pattern will result in 20% faster screw installations.



### Strong-Drive™ WSNTL SUBFLOOR Screw

Ribbed flat head, twin lead thread, sharp point, Yellow zinc, #3 square drive

<b>WSNTLA134SA:</b>	8g x 45mm
<b>WSNTL212SA:</b>	8g x 65mm

- Twin Lead thread for faster driving and superior holding power compared to 3.75mm nails



### WSCBG Underlayment Screw

Wafer head with nibs, coarse thread, Type 17, Class 3 galvanised, #2 undersize square drive

<b>WSCBGA158SA:</b>	8g x 42mm
---------------------	-----------

- Ribbed wafer head with nibs for easier countersinking
- Broad head for greater pulldown



### SSDTH Trim Head Screw

Trim head, 10 TPI box thread, sharp point, 305 stainless steel, #2 square drive

<b>SSDTH2SA:</b>	7g x 50mm
------------------	-----------

- High corrosion resistance
- Trim head for neat appearance



### SSDTH Weatherboard Screw

Trim head, 10 TPI box thread, sharp point, 305 stainless steel, #2 square drive

<b>SSDTH212S:</b>	7g x 65mm
<b>SSDTH3S:</b>	7g x 75mm

- High corrosion resistance
- Trim head for neat appearance



### SS3DSC Bugle-Head Timber Screw

Bugle head, coarse thread, type 17, 305 or 316 stainless steel, #3 square drive

<b>SS3DSC212BS:</b>	10g x 65mm
<b>SS3DSC3BS:</b>	10g x 75mm
<b>SS3DSC212BS316:</b>	10g x 65mm
<b>SS3DSC3BS316:</b>	10g x 75mm

- Type 17 point for easy, straight drive

