

#### TECHNICAL DATASHEET

Code	Description	Size	Colour
41261	Mr Gorilla Graffiti Remover Spray	500ml	Clear
41280	Mr Gorilla Graffiti Remover Spray	500ml	Clear

### 1. Description

Mr Gorilla Graffiti Remover is a user friendly solution designed to remove certain types of graffiti from surfaces. Mr Gorilla Graffiti Remover has been specifically blended to produce a product capable of easily removing graffiti caused by paint, including spray cans and marker pens. This product is very effective in the removal of paint, so where graffiti appears on a pre-painted surface; some of this coating will be removed, along with the graffiti. The solvent blend acts very quickly and has a fast evaporation rate.

### 2. Characteristics

- · Effectively removes graffiti from most surfaces
- · User friendly, pleasant citrus odour
- · Non corrosive, water soluble
- · No fumes, non toxic

### 3. Technical Data

Colour:	Clear
Consistency:	Liquid

## 4. Applications

Removal of graffiti caused by paint, including spray cans. Ideal for bricks, concrete, metal and wooden surfaces. May be used on previously painted surfaces, where the removal of this coating is not a problem.

### 5. Packaging

500ml Trigger Pack

# 6. Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

# 7. Application Instructions

The method of removal depends on the type of surface, and the size and nature of the graffiti. Apply Mr Gorilla Graffiti Remover only to the graffiti. Allow to penetrate the graffiti. Wipe off graffiti with a dry cloth. On stubborn graffiti remove with a brush or scrubbing implement. Rough surfaces such as bricks can be effectively cleaned using Mr Gorilla Graffiti Remover and a brick cleaning brush. Several applications may be necessary, depending on the surface. A small section of the graffiti should be tested prior to total removal.

Soudal recommends preliminary compatibility tests on surfaces on which PU Foams have not been applied previously.

## 8. Health and Safety Recommendation

- · Apply the usual industrial hygiene.
- Ensure adequate ventilation during use. Where appropriate, mask in confined areas. Avoid contact with skin and eyes; wear gloves and glasses during use.

#### Remark

The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.

Last Updated: 2 February 2021

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz