



Cordless Rear Handle Saw
RS002G 260 mm (10-1/4")



40V Li-ion max



High power

10" Rear Handle Saw
(260mm)

Cuts 4x material in a single pass
with max cutting capacity 95 mm.

Lightweight
(with BL4050F)

6.3 kg





High power **BL MOTOR**

High power 40Vmax XGT Li-ion battery and high efficiency BL motor provides easier and more comfortable cutting than corded rear handle saws.

Connectable to vacuum cleaners



Connect a Makita vacuum cleaner to your tool.




Wide hook

- Compatible with up to 66mm width
- The machine can be hung onto, for example, 2x lumbars or I-joint (with a width of 64mm), etc.



Bevel angle up to 56 degrees

Knob and stopper for bevel adjustment with positive stops at 22.5 and 45 degrees.



Auto-start Wireless System



Electric brake system enables you to start the next operation quickly.



Using magnesium diecast

for Base Plate, Blade Case and Safety cover, tool weight has been reduced without loss of durability and power.

Soft start



eXtreme Protection Technology



Cutting Performance

90x300mm Melapi cutting at 0 degrees, cross-cut

(with BL4050F)
80 cuts

The test results depend to a great extent on the hardness of the test material, etc.

40Vmax series movie



40Vmax mechanism movie



This movie was filmed in Japan. Models and specs may vary by country.

40Vmax Sawing lineup

Rear Handle Saw RS001G

Circular Saw HS003G/HS004G



Slide Compound Miter Saw LS002G/LS003G



Accessories

Guide Rule (Rip fence)

Use with thumb screw M6x14 Part No. 265701-9
Part No. 165153-3



Battery Charging Time Reference

	DC40RA (Fast Charging)	DC40RC
BL4050F *15.0Ah	50min	85min
BL4040 4.0Ah	45min	67min
BL4025 2.5Ah	28min	38min
BL4020 2.0Ah	22min	30min

*1 Recommended battery

Cordless Rear Handle Saw

RS002G 260 mm (10-1/4")

Brake	Blade Diameter 260 mm (10-1/4")
Soft Start	Max Cutting Capacity 90°: 95 mm (3-3/4") 45°: 70 mm (2-3/4") 56°: 54.5 mm (2-1/8")
Dust Collecting	No Load Speed (RPM) 4,000
Carrying Case (country-specific)	Vibration Level 2.5m/s ² or less
	Sound Pressure Level 96 dB(A)
	Sound Power Level 107dB(A)
	Dimensions (L x W x H) 489 x 193 x 309 mm (19-1/4 x 7-5/8 x 12-1/8")
	Net weight 5.7 - 6.3 kg (12.6 - 13.9 lbs.)

Standard Equipment:

TCT Saw Blade, Grip, Offset Wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202101