

ULTRAFAST™ DECKING

SCREWS BY BREMICK®



Introducing the all New Bremick Decking Grab 'N' Go Range.

The high performance Bremick UltraFast™ SS304 Decking screws avoid timber splitting, drill cleanly & embed beautifully in decking boards thanks to the Spear Point, Sharks Tooth™ thread and Truss + Trim head designs.

Unique spear point eliminates timber splitting and the need to pre-drill* and countersink hardwood timber.

Advanced Hi-Lo Sharks Tooth™ threads are engineered to drastically reduce driving torque and installation time.

Precision fit Torx+ drive eliminates 'cam out' and facilitates one handed fastening in awkward positions.



STAINLESS STEEL 304
Provides an architectural finish & extreme corrosion protection in severe marine environments.



2x BONUS DRIVER BIT
Every UltraFast™ Grab 'N' Go Box includes 2x 50mm Driver Bits.

Mechanical Properties

| UltraFast™ Decking Screw | Axial Withdrawl Force 35mm embedment F5/H3 Softwood Timber (Radiata Pine) (kN): Note 1 | Axial Withdrawl Force 35mm embedment F17/J3 Hardwood Timber (kN) | Single Shear (kN) | Axial Tensile (kN) | Torsional Nm |
|--------------------------|--|--|-------------------|--------------------|--------------|
| Decking 10G | 5.5 | 7.1 | 4.0 | 6.6 | 4.4 |
| Decking 12G | 6.5 | 7.7 | 5.4 | 9.5 | 7.8 |

1. The Axial withdrawal force required in AS3566.1 at 35mm screw embedment in F5 Radiata Pine is 3.1kN
2. The test results have been conducted under laboratory conditions. Appropriate safety factors must be applied.
3. Drill speed comparisons have been conducted in F5 Radiata Pine.

SHARKS TOOTH™
THREAD FOR SMOOTHER INSTALLATION

TORX DRIVE+
SECURE SOCKET FIT

ULTRAFAST™
NO PRE DRILLING

SPEAR POINT
ELIMINATES SPLITTING™

