

ROTOFLEX®

#9001



#9001

SAFETY
UNISEX
BLACK LEATHER
ELASTIC SIDED



SIZES
3-15

HALF SIZES
9.5-10.5-11.5

GRIPTEK® XHD



300°C
RESISTANT



FUEL OIL
RESISTANT



SLIP
RESISTANT



ELECTRICAL
HAZARD
RESISTANT

SOFTCELL®



WATER
RESISTANT
UPPER



WIDE
FIT

FORTASHIELD



STEEL
TOE CAP

AIRCELL



ZONED
AIRFLOW
FOOTBED

Infinergy®

Made with
Infinergy®
by BASF



CERTIFIED TO:

Standard AS 2210.3:2019
ASTM F2413-18 including EH (Clause 5.6)

Versatile, durable and ready to tackle the day, whatever the terrain. The RotoFlex #9001 features a GripTek® Extra Heavy Duty rubber outsole for optimum underfoot protection, alongside the SoftCell® fit system for unbeatable comfort.

- Black water-resistant leather upper safety boot
- Heavy Duty TPU moulded toe designed for superior leather protection

INFINERGY® —E-TPU, a super elastic energy foam that is soft but resilient, providing enhanced cushioning and reducing the impact of every step.

GRIPTEK® XHD—biomechanically engineered rubber (PUR) outsole designed for optimum grip and stability

- heat resistant to 300 °C
- fuel oil resistant
- excellent abrasion, cut and slip resistance

FORTASHIELD — broad fitting, cut-resistant steel toe cap tested to resist a 200 joule impact.

AIRCELL —uniquely constructed zoned airflow footbed is designed with specialised breathing channels to activate ventilation, moisture control and provide full-body cushioned comfort. The footbed is anti-bacterial, washable and breathable.

SOFTCELL®—the overarching comfort system utilising a combination of specialist materials and the unique biomechanical foot-cradling design to increase stability, balance, comfort and manoeuvrability. Designed to reduce the risk of trips, slips and falls.



Refer to blundstone.co.nz for further details of the 30 day comfort guarantee and the manufacturer's warranty.

PU - Polyurethane | **TPU** - Thermoplastic Polyurethane
EVA - Ethel Vinyl Acetate | **PUR** - Polyurethane & Rubber

NZ-9001-0523