

FUNCTIONAL BENEFITS



Dimensional Stability




Easy To Clean



Antimicrobial Panel



Impact Resistant



Easy To Cut

- No edge sealing or painting required.
- UV Coated in NZ.
- Currently being BRANZ Appraised.
- Completely impervious.
- No bowing, warping, swelling or rotting.
- Extremely durable, very strong & impact resistant.
- Incredibly dimensionally stable, flat with uniform thickness.
- Smooth surface that resists marks, stains, steam & moisture.
- Easy to cut using standard carpentry tooling, hand saw or score & snap.
- Easy to install. One person installation.

APPLICATIONS



Wet Area



Dry Area



Vertical Wall Linings



On Ceilings



Kitchen Splashback*

- Wall panelling, ceilings, feature walls, partitioning, kitchen splashbacks* & laundry walls.
- For long lasting performance in homes, hospitals, restaurants, research facilities & commercial spaces.

*Refer to Technical Installation Manual for Splashback compliance.

JOINTERS

- Panels available in a range of contemporary colours & finishes with colour matched aluminium jointers.

INSTALLATION

- Full installation instructions can be found in the latest Technical Installation Manual. Always follow & adhere to these instructions. Download Manual at laminex.co.nz (from 30 Sep 2024).



WARRANTY



15 Year Warranty

FIRE RATING CLASSIFICATION



Group 3

DECOR		SHEET SIZE (mm)	THICKNESS	FINISH	MATCHING JOINTER	FR CLASS.
Polar		2700x1200 2400x1200 2400x900	4.5mm	Gloss Matte	✓	Group 3
Shell		2700x1200	4.5mm	Gloss Matte	✓	Group 3
Canvas		2700x1200	4.5mm	Gloss Matte	✓	Group 3
Summit		2700x1200 2400x1200	4.5mm	Gloss Matte	✓	Group 3
Mineral		2700x1200	4.5mm	Gloss	✓	Group 3
Meteor		2700x1200	4.5mm	Gloss Matte	✓	Group 3

NOTE: All measurements are nominal.

LNZ300824